

Technical Data Sheet

Date: 03/11/2022

5x32A CEE Norm Angled Plug

Ref. No: 3007-302-1600



Pack Unit

10



Weight

225 gr.




Technical Informations

Quick Connection

Ampere	32A
Voltage	380 - 415 V. AC
Hertz	50 - 60 Hz
Protection Class	IP 44
Clock Position	6h
Number Of Poles	5 (3P + N + E)
Contact Material	Brass (CuZn)
Housing Material	PA6
Connection Type	Quick
Operation Temp. (-25 / + 40 IEC 60309)	-25 / +80 (1 hour -100° C)

Dimensions

a	129	Øk	11-20,5
b	79	Cable Diameter (Min.)	2,5 mm²
c	70	Cable Diameter (Max.)	10 mm²
d	110		
e	20		



Different Earth Contact Positions (Clock Positions)

3007-302-1100-2h	3007-302-1600-3h	3007-302-0700-4h	3007-302-0300-5h	3007-302-1600	3007-302-0300-7h	3007-302-0900-9h	3007-302-1600-11h



Tel: +90 232 880 90 01
Fax: +90 232 880 90 02



info@tpelectric.com.tr



Kemalpaşa O.S.B. 600 Sk. No:364
35730 Kemalpaşa - İZMİR / TÜRKİYE